

BEAst Supply Delivery schedule response



XML Guideline

Elements	St	Occurrence	Annotations
DeliveryScheduleResponse			Type: ComplexType Description: This business transaction is used by customers to notify a supplier if a received delivery shedule is accepted. Name: Delivery schedule response Example: This business transaction is used by suppliers to notify a customer if a received delivery shedule is accepted.
xs:sequence	M	1..1	Type: ContentModel
DeliveryScheduleResponseHeader	M	1..1	Type: DeliveryScheduleResponseHeader Name: Header Element
xs:sequence	M	1..1	Type: ContentModel
DeliveryScheduleResponseID	M	1..1	Type: sddb:DeliveryScheduleResponseID Length: 0 .. 17 Format: sddb:String17 Name: Delivery schedule response ID Example: 61827636 Element
DocumentDateTime	M	1..1	Type: sddb:DocumentDateTime Pattern: \d{12} Format: sddb:DateAndShortTime Name: Document date time Example: 201212181024 Element
DeliveryScheduleResponseStatus	M	1..1	Type: sddb:DeliveryScheduleResponseStatus Length: 0 .. 3 Format: sddb:String3 Description: Codes that can be used are: Accepted = "OK", Not accepted = "NOK" Name: Delivery schedule response status Example: OK Element
SupplierRemark	O	0..1	Type: sddb:SupplierRemark Length: 0 .. 512 Format: sddb:String512 Name: Suppliers remarks Example: Nytt plusgironr 772064-9 gäller från 2009-05-01 Element
ReferenceToDocument	M	1..1	Type: sddb:ReferenceToDocument Name: Document references Element
xs:sequence	M	1..1	Type: ContentModel
ReferenceToDeliverySchedule	M	1..1	Type: sddb:ReferenceToDeliverySchedule Element

St = Status: M=Mandatory, O=Optional

BEAst Supply Delivery schedule response



XML Guideline

Elements	St	Occurrence	Annotations
			Length: 0 .. 17 Format: sddb:String17 Name: Reference to delivery schedule Example: 61827623
ReferenceToDeliveryScheduleVersion	O	0..1	Type: sddb:ReferenceToDeliveryScheduleVersion FractionDigits: 0 TotalDigits: 2 Format: sddb:Integer2 Name: Reference to delivery schedule version Example: 2 TotalDigits: 2
BuyerNeB	M	1..1	Type: sddb:BuyerNeB Name: Buyer
xs:sequence	M	1..1	Type: ContentModel
Buyer	O	0..1	Type: sddb:Buyer Pattern: \d{13} Format: sddb:GLN Name: Buyer Example: 7381030000028
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 7651235
SupplierNeB	M	1..1	Type: sddb:SupplierNeB Name: Supplier
xs:sequence	M	1..1	Type: ContentModel
Supplier	O	0..1	Type: sddb:Supplier Pattern: \d{13} Format: sddb:GLN Name: Supplier Example: 7381030000032
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier

St = Status: M=Mandatory, O=Optional

BEAst Supply Delivery schedule response



XML Guideline

Elements	St	Occurrence	Annotations	
SuppliersContact	M	1..1	Example: 7652344 Type: sddb:SuppliersContact Name: Supplier's contact	<i>Element</i>
xs:sequence	M	1..1	Type: sddb:Name	<i>ContentModel</i>
Name	O	0..1	Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Lars Larsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4687681590	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: lars.larsson@trakompaniet.se	<i>Element</i>

St = Status: M=Mandatory, O=Optional