

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectList	M		Type: ProjectList	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
ProjectHeader	M	1..1	Type: ProjectHeader	<i>Element</i>
			Name: Project header	
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
MessageNumber	M	1..1	Type: sddb:MessageNumber	<i>Element</i>
			Length: 0 .. 14	
			Format: sddb:String14	
			Name: Message number	
			Example: 123456	
DocumentDate	M	1..1	Type: sddb:DocumentDate	<i>Element</i>
			Pattern: \d{8}	
			Format: sddb:Date	
			Name: Document date	
			Example: 20150601	
InterchangeSenderParty	M	1..1	Type: sddb:InterchangeSenderParty	<i>Element</i>
			Description: One of T3002 and T6001 must be used.	
			Name: Interchange sender	
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
InterchangeSender	O	0..1	Type: sddb:InterchangeSender	<i>Element</i>
			Pattern: \d{13}	
			Format: sddb:GLN	
			Name: Interchange sender	
			Example: 7350047100028	
AddressNeB	O	0..1	Type: sddb:AddressNeB	<i>Element</i>
			Name: Id number/Name and address	
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier	<i>Element</i>
			Length: 0 .. 35	
			Format: sddb:PartyIdentifier	
			Name: Partner Identifier	
			Example: 56987	
PartyName	O	0..1	Type: sddb:PartyName	<i>Element</i>
			Length: 0 .. 35	
			Format: sddb:PartyName	

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
InterchangeRecipientParty	O	0..1	Name: Party name Example: Byggtreprenader Sverige AB Type: sddb:InterchangeRecipientParty Description: One of T3003 and T6001 must be used.	<i>Element</i>
xs:sequence	M	1..1	Name: Interchange recipient party	<i>ContentModel</i>
InterchangeRecipient	O	0..1	Type: sddb:InterchangeRecipient Pattern: \d{13} Format: sddb:GLN	<i>Element</i>
AddressNeB	O	0..1	Name: Interchange recipient Example: 7350036100007 Type: sddb:AddressNeB	<i>Element</i>
xs:sequence	M	1..1	Name: Id number/Name and address	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier	<i>Element</i>
PartyName	O	0..1	Name: Partner Identifier Example: 7655678 Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName	<i>Element</i>
ProjectLine	M	1..unbounded	Name: Party name Example: Byggprodukter AB Type: ProjectLine Description: Repeated per project number.	<i>Element</i>
xs:sequence	M	1..1	Name: Project line	<i>ContentModel</i>
ProjectNumber	M	1..1	Type: sddb:ProjectNumber Length: 0 .. 70 Format: sddb:String70	<i>Element</i>
ProjectName	O	0..1	Name: Project number Example: 6411-001 Type: sddb:ProjectName Length: 0 .. 50	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectStatus	O	0..1	Format: sddb:String50	<i>Element</i>
			Name: Project name Example: Solrosgränd	
ProjectType	O	0..1	Type: sddb:ProjectStatus Length: 0 .. 2 Format: sddb:ProjectStatus	<i>Element</i>
			Name: Project status Example: AK	
			Code/Description	
			AK	Aktivt
			AV	Avslutat
			PL	Planerat
Region	O	0..1	Type: sddb:ProjectType Length: 0 .. 3 Format: sddb:ProjectType	<i>Element</i>
			Name: Project type Example: NYP	
			Code/Description	
			NYP	Nyproduktion
			ROT	ROT projekt
			VÄG	Vägbygge
Municipality	O	0..1	Type: sddb:Region Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
			Name: Region Example: Göteborg	
ProjectStartDate	O	0..1	Type: sddb:Municipality Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
			Name: Municipality Example: Kungsbacka	
			Type: sddb:ProjectStartDate Pattern: \d{8} Format: sddb:Date	<i>Element</i>
			Name: Project period, start date Example: 20150101	

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectEndDate	O	0..1	Type: sddb:ProjectEndDate Pattern: \d{8} Format: sddb:Date Name: Project period, end date Example: 20160601	<i>Element</i>
ContractSum	O	0..1	Type: sddb:ContractSum FractionDigits: 0 TotalDigits: 10 Format: sddb:Integer10 Description: Million Swedish kronor Name: Contract sum Example: 105	TotalDigits: 10 <i>Element</i>
GuaranteePeriod	O	0..1	Type: sddb:GuaranteePeriod FractionDigits: 0 TotalDigits: 5 Format: sddb:Integer5 Name: Guarantee period Example: 36	TotalDigits: 5 <i>Element</i>
ProjectOwner	M	1..1	Type: sddb:ProjectOwner Description: One of T6385 and T6001 must be used. Name: Project owner	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
ProjectOwningParty	O	0..1	Type: sddb:ProjectOwningParty Pattern: \d{13} Format: sddb:GLN Name: Project owning party Example: 7381020000036	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 85214	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Byggentreprenader Väst	<i>Element</i>
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department Example: 3	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Name: Street name Example: Lillavägen 1	<i>Element</i>
Building	O	0..1	Type: sddb:Building Length: 0 .. 35 Format: sddb:Building Name: Building Example: 5	<i>Element</i>
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Name: Postal box number Example: 73	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Name: City name Example: Staden	<i>Element</i>
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Name: Postal code Example: 45678	<i>Element</i>
CountryCode	O	0..1	Type: sddb:CountryCode	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	
InvoiceeNeB	O	0..1	Type: sddb:InvoiceeNeB Name: Invoice	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Invoicee	O	0..1	Type: sddb:Invoicee Pattern: \d{13} Format: sddb:GLN Name: Invoice Example: 7381030000067	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 7655678	<i>Element</i>
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Factoring AB	<i>Element</i>
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department Example: Ekonomiavd	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Description: Invoice address Name: Street name Example: Fakturavägen 1	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Description: Invoice address Name: Postal box number Example: 1	Element
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Description: Invoice address Name: City name Example: Fstad	Element
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Description: Invoice address Name: Postal code Example: 42159	Element
CountryCode	O	0..1	Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	Element
DeliveryNeB	O	0..1	Type: sddb:DeliveryNeB Description: If other than project owning party. Name: Delivery party	Element
xs:sequence	M	1..1	Type:	ContentModel
DeliveryParty	O	0..1	Type: sddb:DeliveryParty Pattern: \d{13} Format: sddb:GLN Name: Delivery party Example: 738105000041	Element
DeliveryPlaceLocation	O	0..1	Type: sddb:DeliveryPlaceLocation Format: xs:string Name: Place of delivery, specified	Element

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
EntryCode	O	0..1	Example: Xstad Type: sddb:EntryCode Length: 0 .. 12 Format: sddb:String12 Name: Entry code Example: 4598	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Name: Street name Example: Tallvägen	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Name: City name Example: Xstad	<i>Element</i>
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Name: Postal code Example: 23192	<i>Element</i>
CountryCode	O	0..1	Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	<i>Element</i>
ReceiverCoordinateX	O	0..1	Type: sddb:ReceiverCoordinateX Length: 0 .. 25 Format: sddb:String25 Name: Receiver coordinate X Example: 18.06468	<i>Element</i>
ReceiverCoordinateY	O	0..1	Type: sddb:ReceiverCoordinateY Length: 0 .. 25	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Format: sddb:String25 Name: Receiver coordinate Y Example: 59.330619	
DeliveryContact	O	0..1	Type: sddb:DeliveryContact Name: Delivery contact	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Karla Svensson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4687652220	<i>Element</i>
SMSNumber	O	0..1	Type: sddb:SMSNumber Length: 0 .. 25 Format: sddb:String25 Name: SMS number Example: +46709382695	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: karla@skoogs.se	<i>Element</i>
ProjectContact1SiteManager	O	0..1	Type: sddb:ProjectContact1SiteManager Name: Project contact 1, Site manager	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Lena Nilsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Format: sddb:String25 Name: Phone number Example: +4682251590	
— EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512	<i>Element</i>
— ID06	O	0..1	Name: Email address Example: lena@byggentreprenader.se Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
— ProjectContact2ProjectPurchaser	O	0..1	Name: Identification code ID06 Example: AA-0711-123456 Type: sddb:ProjectContact2ProjectPurchaser	<i>Element</i>
— xs:sequence	M	1..1	Name: Project contact 2, Project Purchaser Type: sddb:ProjectContact2ProjectPurchaser	<i>ContentModel</i>
— Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
— PhoneNumber	O	0..1	Name: Name Example: Eva Svensson Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
— EmailAddress	O	0..1	Name: Phone number Example: +4682251591 Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512	<i>Element</i>
— ID06	O	0..1	Name: Email address Example: eva@byggentreprenader.se Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
			Name: Identification code ID06 Example: AB-0711-123467	

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectContact3ProjectManager	O	0..1	Type: sddb:ProjectContact3ProjectManager Name: Project contact 3, Project manager	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Erik Larsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4682251592	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: erik@byggentreprenader.se	<i>Element</i>
ID06	O	0..1	Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06 Example: AC-0711-123478	<i>Element</i>
ProjectContact4ProductionManager	O	0..1	Type: sddb:ProjectContact4ProductionManager Name: Project contact 4, Production manager	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Sven Nilsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4682251593	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: sven@byggentreprenader.se	<i>Element</i>
ID06	O	0..1	Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06 Example: AD-0711-123489	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectHeader			Type: Name: Project header	<i>ComplexType</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
MessageNumber	M	1..1	Type: sddb:MessageNumber Length: 0 .. 14 Format: sddb:String14 Name: Message number Example: 123456	<i>Element</i>
DocumentDate	M	1..1	Type: sddb:DocumentDate Pattern: \d{8} Format: sddb:Date Name: Document date Example: 20150601	<i>Element</i>
InterchangeSenderParty	M	1..1	Type: sddb:InterchangeSenderParty Description: One of T3002 and T6001 must be used. Name: Interchange sender	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
InterchangeSender	O	0..1	Type: sddb:InterchangeSender Pattern: \d{13} Format: sddb:GLN Name: Interchange sender Example: 7350047100028	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 56987	<i>Element</i>
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Byggtreprenader Sverige AB	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Name: Street name	<i>Element</i>
Building	O	0..1	Type: sddb:Building Length: 0 .. 35 Format: sddb:Building Name: Building	<i>Element</i>
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Name: Postal box number	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Name: City name	<i>Element</i>
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Name: Postal code	<i>Element</i>
CountryCode	O	0..1	Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded	<i>Element</i>
SenderCoordinateX	O	0..1	Type: sddb:SenderCoordinateX Length: 0 .. 25 Format: sddb:String25 Name: Sender coordinate X Example: 17.680456	<i>Element</i>
SenderCoordinateY	O	0..1	Type: sddb:SenderCoordinateY Length: 0 .. 25 Format: sddb:String25	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ReceiverCoordinateX	O	0..1	Name: Sender coordinate Y Example: 59.846599 Type: sddb:ReceiverCoordinateX Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
ReceiverCoordinateY	O	0..1	Name: Receiver coordinate X Example: 18.06468 Type: sddb:ReceiverCoordinateY Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
GeographicPoint	O	0..1	Name: Receiver coordinate Y Example: 59.330619 Type: sddb:GeographicPoint	<i>Element</i>
xs:sequence	M	1..1	Name: Geographic point Type:	<i>ContentModel</i>
GeographicalCo-ordinate1	O	0..1	Type: sddb:GeographicalCo-ordinate1 Length: 0 .. 30 Format: sddb:String30	<i>Element</i>
GeographicalCo-ordinate2	O	0..1	Name: Geographical co-ordinate 1 Type: sddb:GeographicalCo-ordinate2 Length: 0 .. 30 Format: sddb:String30	<i>Element</i>
GeographicalCo-ordinate3	O	0..1	Name: Geographical co-ordinate 2 Type: sddb:GeographicalCo-ordinate3 Length: 0 .. 30 Format: sddb:String30	<i>Element</i>
GeographicCo-ordinateSystemCode	O	0..1	Name: Geographical co-ordinate 3 Type: sddb:GeographicCo-ordinateSystemCode Length: 0 .. 10 Format: sddb:GeographicCo-ordinateSystemCode	<i>Element</i>
InterchangeRecipientParty	O	0..1	Name: Geographic co-ordinate system, code Type: sddb:InterchangeRecipientParty Description: One of T3003 and T6001 must be used.	<i>Element</i>
xs:sequence	M	1..1	Name: Interchange recipient party Type:	<i>ContentModel</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
InterchangeRecipient	O	0..1	Type: sddb:InterchangeRecipient Pattern: \d{13} Format: sddb:GLN Name: Interchange recipient Example: 7350036100007	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 7655678	<i>Element</i>
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Byggprodukter AB	<i>Element</i>
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Name: Street name	<i>Element</i>
Building	O	0..1	Type: sddb:Building Length: 0 .. 35 Format: sddb:Building Name: Building	<i>Element</i>
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Name: Postal box number	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
PostalCodeNeB	O	0..1	Format: sddb:CityName Name: City name Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17	<i>Element</i>
CountryCode	O	0..1	Name: Postal code Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType	<i>Element</i>
SenderCoordinateX	O	0..1	Name: Country, coded Type: sddb:SenderCoordinateX Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
SenderCoordinateY	O	0..1	Name: Sender coordinate X Example: 17.680456 Type: sddb:SenderCoordinateY Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
ReceiverCoordinateX	O	0..1	Name: Sender coordinate Y Example: 59.846599 Type: sddb:ReceiverCoordinateX Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
ReceiverCoordinateY	O	0..1	Name: Receiver coordinate X Example: 18.06468 Type: sddb:ReceiverCoordinateY Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
GeographicPoint	O	0..1	Name: Receiver coordinate Y Example: 59.330619 Type: sddb:GeographicPoint	<i>Element</i>
xs:sequence	M	1..1	Name: Geographic point Type:	<i>ContentModel</i>
GeographicalCo-ordinate1	O	0..1	Type: sddb:GeographicalCo-ordinate1 Length: 0 .. 30 Format: sddb:String30	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
GeographicalCo-ordinate2	O	0..1	Name: Geographical co-ordinate 1 Type: sddb:GeographicalCo-ordinate2 Length: 0 .. 30 Format: sddb:String30	<i>Element</i>
GeographicalCo-ordinate3	O	0..1	Name: Geographical co-ordinate 2 Type: sddb:GeographicalCo-ordinate3 Length: 0 .. 30 Format: sddb:String30	<i>Element</i>
GeographicCo-ordinateSystemCode	O	0..1	Name: Geographical co-ordinate 3 Type: sddb:GeographicCo-ordinateSystemCode Length: 0 .. 10 Format: sddb:GeographicCo-ordinateSystemCode Name: Geographic co-ordinate system, code	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectLine			Type: Name: Project line	<i>ComplexType</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
ProjectNumber	M	1..1	Type: sddb:ProjectNumber Length: 0 .. 70 Format: sddb:String70 Name: Project number Example: 6411-001	<i>Element</i>
ProjectName	O	0..1	Type: sddb:ProjectName Length: 0 .. 50 Format: sddb:String50 Name: Project name Example: Solrosgränd	<i>Element</i>
ProjectStatus	O	0..1	Type: sddb:ProjectStatus Length: 0 .. 2 Format: sddb:ProjectStatus Name: Project status Example: AK	<i>Element</i>
ProjectType	O	0..1	Type: sddb:ProjectType Length: 0 .. 3 Format: sddb:ProjectType Name: Project type Example: NYP	<i>Element</i>
Region	O	0..1	Type: sddb:Region Length: 0 .. 25 Format: sddb:String25 Name: Region Example: Göteborg	<i>Element</i>
Municipality	O	0..1	Type: sddb:Municipality Length: 0 .. 25 Format: sddb:String25 Name: Municipality Example: Kungsbacka	<i>Element</i>
ProjectStartDate	O	0..1	Type: sddb:ProjectStartDate Pattern: \d{8} Format: sddb:Date	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectEndDate	O	0..1	Name: Project period, start date Example: 20150101 Type: sddb:ProjectEndDate Pattern: \d{8} Format: sddb:Date	<i>Element</i>
ContractSum	O	0..1	Name: Project period, end date Example: 20160601 Type: sddb:ContractSum FractionDigits: 0 TotalDigits: 10 Format: sddb:Integer10	TotalDigits: 10 <i>Element</i>
GuaranteePeriod	O	0..1	Name: Contract sum Example: 105 Type: sddb:GuaranteePeriod FractionDigits: 0 TotalDigits: 5 Format: sddb:Integer5	TotalDigits: 5 <i>Element</i>
ProjectOwner	M	1..1	Name: Guarantee period Example: 36 Type: sddb:ProjectOwner	<i>Element</i>
xs:sequence	M	1..1	Description: Project owner One of T6385 and T6001 must be used.	<i>ContentModel</i>
ProjectOwningParty	O	0..1	Name: Project owner Type: sddb:ProjectOwningParty Pattern: \d{13} Format: sddb:GLN	<i>Element</i>
AddressNeB	O	0..1	Name: Project owning party Example: 7381020000036 Type: sddb:AddressNeB	<i>Element</i>
xs:sequence	M	1..1	Name: Id number/Name and address	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 85214	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Byggentreprenader Väst	<i>Element</i>
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department Example: 3	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Name: Street name Example: Lillavägen 1	<i>Element</i>
Building	O	0..1	Type: sddb:Building Length: 0 .. 35 Format: sddb:Building Name: Building Example: 5	<i>Element</i>
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Name: Postal box number Example: 73	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Name: City name Example: Staden	<i>Element</i>
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Name: Postal code Example: 45678	<i>Element</i>
CountryCode	O	0..1	Type: sddb:CountryCode	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	
— SenderCoordinateX	O	0..1	Type: sddb:SenderCoordinateX Length: 0 .. 25 Format: sddb:String25 Name: Sender coordinate X Example: 17.680456	<i>Element</i>
— SenderCoordinateY	O	0..1	Type: sddb:SenderCoordinateY Length: 0 .. 25 Format: sddb:String25 Name: Sender coordinate Y Example: 59.846599	<i>Element</i>
— ReceiverCoordinateX	O	0..1	Type: sddb:ReceiverCoordinateX Length: 0 .. 25 Format: sddb:String25 Name: Receiver coordinate X Example: 18.06468	<i>Element</i>
— ReceiverCoordinateY	O	0..1	Type: sddb:ReceiverCoordinateY Length: 0 .. 25 Format: sddb:String25 Name: Receiver coordinate Y Example: 59.330619	<i>Element</i>
— GeographicPoint	O	0..1	Type: sddb:GeographicPoint Name: Geographic point	<i>Element</i>
— xs:sequence	M	1..1	Type:	<i>ContentModel</i>
— GeographicalCo-ordinate1	O	0..1	Type: sddb:GeographicalCo-ordinate1 Length: 0 .. 30 Format: sddb:String30 Name: Geographical co-ordinate 1	<i>Element</i>
— GeographicalCo-ordinate2	O	0..1	Type: sddb:GeographicalCo-ordinate2 Length: 0 .. 30 Format: sddb:String30 Name: Geographical co-ordinate 2	<i>Element</i>
— GeographicalCo-ordinate3	O	0..1	Type: sddb:GeographicalCo-ordinate3	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Length: 0 .. 30 Format: sddb:String30	
GeographicCo-ordinateSystemCode	O	0..1	Name: Geographical co-ordinate 3 Type: sddb:GeographicCo-ordinateSystemCode Length: 0 .. 10 Format: sddb:GeographicCo-ordinateSystemCode	<i>Element</i>
InvoiceeNeB	O	0..1	Name: Geographic co-ordinate system, code Type: sddb:InvoiceeNeB	<i>Element</i>
xs:sequence	M	1..1	Name: Invoice Type:	<i>ContentModel</i>
Invoicee	O	0..1	Type: sddb:Invoicee Pattern: \d{13} Format: sddb:GLN Name: Invoice Example: 7381030000067	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 7655678	<i>Element</i>
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Factoring AB	<i>Element</i>
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department Example: Ekonomiavd	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations
PostalBoxNumber	O	0..1	<p>Name: Street name Example: Fakturavägen 1 Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber</p> <p>Name: Postal box number Example: 1</p>
CityName	O	0..1	<p>Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName</p> <p>Name: City name Example: Fstad</p>
PostalCodeNeB	O	0..1	<p>Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17</p> <p>Name: Postal code Example: 42159</p>
CountryCode	O	0..1	<p>Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType</p> <p>Name: Country, coded Example: SE</p>
SenderCoordinateX	O	0..1	<p>Type: sddb:SenderCoordinateX Length: 0 .. 25 Format: sddb:String25</p> <p>Name: Sender coordinate X Example: 17.680456</p>
SenderCoordinateY	O	0..1	<p>Type: sddb:SenderCoordinateY Length: 0 .. 25 Format: sddb:String25</p> <p>Name: Sender coordinate Y Example: 59.846599</p>
ReceiverCoordinateX	O	0..1	<p>Type: sddb:ReceiverCoordinateX Length: 0 .. 25 Format: sddb:String25</p> <p>Name: Receiver coordinate X</p>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ReceiverCoordinateY	O	0..1	Example: 18.06468 Type: sddb:ReceiverCoordinateY Length: 0 .. 25 Format: sddb:String25 Name: Receiver coordinate Y Example: 59.330619	<i>Element</i>
InvoceesContact	O	0..1	Type: sddb:InvoceesContact Name: Invoicee's contact	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Eva Svensson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4681901590	<i>Element</i>
SMSNumber	O	0..1	Type: sddb:SMSNumber Length: 0 .. 25 Format: sddb:String25 Name: SMS number Example: +4681901590	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: eva@factoring.se	<i>Element</i>
ID06	O	0..1	Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06	<i>Element</i>
TaxReference	O	0..1	Type: sddb:TaxReference Description: Tax reference Name: Reference to tax and organization number	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
InvoiceeVATRegistrationNumber	O	0..1	Type: sddb:InvoiceeVATRegistrationNumber Length: 0 .. 35 Format: sddb:String35 Name: Invoiceer's VAT registration number Example: SE556048581801	<i>Element</i>
RegistrationNumber	O	0..1	Type: sddb:RegistrationNumber Length: 0 .. 35 Format: sddb:String35 Name: Company registrerings number Example: 5564538188	<i>Element</i>
FiscalNumber	O	0..1	Type: sddb:FiscalNumber Length: 0 .. 35 Format: sddb:String35 Name: Fiscal number Example: 8546251972	<i>Element</i>
GovernmentReferenceNumber	O	0..1	Type: sddb:GovernmentReferenceNumber Length: 0 .. 35 Format: sddb:String35 Name: Government referencenumber Example: 5566583512	<i>Element</i>
TaxRegistrationNumber	O	0..1	Type: sddb:TaxRegistrationNumber Length: 0 .. 35 Format: sddb:String35 Name: Tax registration number Example: SE556453818801	<i>Element</i>
DeliveryNeB	O	0..1	Type: sddb:DeliveryNeB Description: If other than project owning party. Name: Delivery party	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
DeliveryParty	O	0..1	Type: sddb:DeliveryParty Pattern: \d{13} Format: sddb:GLN Name: Delivery party Example: 738105000041	<i>Element</i>
DeliveryPlaceLocation	O	0..1	Type: sddb:DeliveryPlaceLocation	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
EntryCode	O	0..1	Format: xs:string Name: Place of delivery, specified Example: Xstad Type: sddb:EntryCode Length: 0 .. 12 Format: sddb:String12	<i>Element</i>
AddressNeB	O	0..1	Name: Entry code Example: 4598 Type: sddb:AddressNeB	<i>Element</i>
xs:sequence	M	1..1	Name: Id number/Name and address Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier	<i>Element</i>
PartyName	O	0..1	Name: Partner Identifier Example: 7228798 Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName	<i>Element</i>
Department	O	0..1	Name: Party name Example: Skoogs lagerhall Type: sddb:Department Length: 0 .. 35 Format: sddb:Department	<i>Element</i>
StreetName	O	0..1	Name: Department Example: Lager Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName	<i>Element</i>
Building	O	0..1	Name: Street name Example: Tallvägen Type: sddb:Building Length: 0 .. 35 Format: sddb:Building	<i>Element</i>
			Name: Building Example: Hall A	

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Name: Postal box number Example: 1	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Name: City name Example: Xstad	<i>Element</i>
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Name: Postal code Example: 23192	<i>Element</i>
CountryCode	O	0..1	Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	<i>Element</i>
SenderCoordinateX	O	0..1	Type: sddb:SenderCoordinateX Length: 0 .. 25 Format: sddb:String25 Name: Sender coordinate X Example: 17.680456	<i>Element</i>
SenderCoordinateY	O	0..1	Type: sddb:SenderCoordinateY Length: 0 .. 25 Format: sddb:String25 Name: Sender coordinate Y Example: 59.846599	<i>Element</i>
ReceiverCoordinateX	O	0..1	Type: sddb:ReceiverCoordinateX Length: 0 .. 25 Format: sddb:String25 Name: Receiver coordinate X Example: 18.06468	<i>Element</i>
ReceiverCoordinateY	O	0..1	Type: sddb:ReceiverCoordinateY	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Length: 0 .. 25 Format: sddb:String25 Name: Receiver coordinate Y Example: 59.330619	
DeliveryContact	O	0..1	Type: sddb:DeliveryContact Name: Delivery contact	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Karla Svensson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4687652220	<i>Element</i>
SMSNumber	O	0..1	Type: sddb:SMSNumber Length: 0 .. 25 Format: sddb:String25 Name: SMS number Example: +46709382695	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: karla@skoogs.se	<i>Element</i>
ID06	O	0..1	Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06	<i>Element</i>
ProjectContact1SiteManager	O	0..1	Type: sddb:ProjectContact1SiteManager Name: Project contact 1, Site manager	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
— PhoneNumber	O	0..1	Format: sddb:String35 Name: Name Example: Lena Nilsson Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
— SMSNumber	O	0..1	Name: Phone number Example: +4682251590 Type: sddb:SMSNumber Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
— EmailAddress	O	0..1	Name: SMS number Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512	<i>Element</i>
— ID06	O	0..1	Name: Email address Example: lena@byggentreprenader.se Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
ProjectContact2ProjectPurchaser	O	0..1	Name: Identification code ID06 Example: AA-0711-123456 Type: sddb:ProjectContact2ProjectPurchaser	<i>Element</i>
— xs:sequence	M	1..1	Name: Project contact 2, Project Purchaser Type: sddb>Name	<i>ContentModel</i>
— Name	O	0..1	Example: Eva Svensson Type: sddb:String35 Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
— PhoneNumber	O	0..1	Name: Name Example: Eva Svensson Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
— SMSNumber	O	0..1	Name: Phone number Example: +4682251591 Type: sddb:SMSNumber	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Length: 0 .. 25 Format: sddb:String25	
EmailAddress	O	0..1	Name: SMS number Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512	<i>Element</i>
ID06	O	0..1	Name: Email address Example: eva@byggentreprenader.se Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
ProjectContact3ProjectManager	O	0..1	Name: Identification code ID06 Example: AB-0711-123467 Type: sddb:ProjectContact3ProjectManager	<i>Element</i>
xs:sequence	M	1..1	Name: Project contact 3, Project manager Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
PhoneNumber	O	0..1	Name: Name Example: Erik Larsson Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
SMSNumber	O	0..1	Name: Phone number Example: +4682251592 Type: sddb:SMSNumber Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
EmailAddress	O	0..1	Name: SMS number Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512	<i>Element</i>
ID06	O	0..1	Name: Email address Example: erik@byggentreprenader.se Type: sddb:ID06	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06 Example: AC-0711-123478	
ProjectContact4ProductionManager	O	0..1	Type: sddb:ProjectContact4ProductionManager Name: Project contact 4, Production manager	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Sven Nilsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4682251593	<i>Element</i>
SMSNumber	O	0..1	Type: sddb:SMSNumber Length: 0 .. 25 Format: sddb:String25 Name: SMS number	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: sven@byggentreprenader.se	<i>Element</i>
ID06	O	0..1	Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06 Example: AD-0711-123489	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectList			Type:	<i>ComplexType</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
ProjectHeader	M	1..1	Type: ProjectHeader Name: Project header	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
MessageNumber	M	1..1	Type: sddb:MessageNumber Length: 0 .. 14 Format: sddb:String14 Name: Message number Example: 123456	<i>Element</i>
DocumentDate	M	1..1	Type: sddb:DocumentDate Pattern: \d{8} Format: sddb:Date Name: Document date Example: 20150601	<i>Element</i>
InterchangeSenderParty	M	1..1	Type: sddb:InterchangeSenderParty Description: <i>One of T3002 and T6001 must be used.</i> Name: Interchange sender	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
InterchangeSender	O	0..1	Type: sddb:InterchangeSender Pattern: \d{13} Format: sddb:GLN Name: Interchange sender Example: 7350047100028	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 56987	<i>Element</i>
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
InterchangeRecipientParty	O	0..1	Name: Party name Example: Byggtreprenader Sverige AB Type: sddb:InterchangeRecipientParty Description: One of T3003 and T6001 must be used.	<i>Element</i>
xs:sequence	M	1..1	Name: Interchange recipient party	<i>ContentModel</i>
InterchangeRecipient	O	0..1	Type: sddb:InterchangeRecipient Pattern: \d{13} Format: sddb:GLN	<i>Element</i>
AddressNeB	O	0..1	Name: Interchange recipient Example: 7350036100007 Type: sddb:AddressNeB	<i>Element</i>
xs:sequence	M	1..1	Name: Id number/Name and address	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier	<i>Element</i>
PartyName	O	0..1	Name: Partner Identifier Example: 7655678 Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName	<i>Element</i>
ProjectLine	M	1..unbounded	Name: Party name Example: Byggprodukter AB Type: ProjectLine Description: Repeated per project number.	<i>Element</i>
xs:sequence	M	1..1	Name: Project line	<i>ContentModel</i>
ProjectNumber	M	1..1	Type: sddb:ProjectNumber Length: 0 .. 70 Format: sddb:String70	<i>Element</i>
ProjectName	O	0..1	Name: Project number Example: 6411-001 Type: sddb:ProjectName Length: 0 .. 50	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectStatus	O	0..1	Format: sddb:String50	<i>Element</i>
			Name: Project name Example: Solrosgränd	
ProjectType	O	0..1	Type: sddb:ProjectStatus Length: 0 .. 2 Format: sddb:ProjectStatus	<i>Element</i>
			Name: Project status Example: AK	
			Code/Description	
			AK	Aktivt
			AV	Avslutat
			PL	Planerat
Region	O	0..1	Type: sddb:ProjectType Length: 0 .. 3 Format: sddb:ProjectType	<i>Element</i>
			Name: Project type Example: NYP	
			Code/Description	
			NYP	Nyproduktion
			ROT	ROT projekt
			VÄG	Vägbygge
Municipality	O	0..1	Type: sddb:Region Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
			Name: Region Example: Göteborg	
ProjectStartDate	O	0..1	Type: sddb:Municipality Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
			Name: Municipality Example: Kungsbacka	
			Type: sddb:ProjectStartDate Pattern: \d{8} Format: sddb:Date	<i>Element</i>
			Name: Project period, start date Example: 20150101	

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectEndDate	O	0..1	Type: sddb:ProjectEndDate Pattern: \d{8} Format: sddb:Date Name: Project period, end date Example: 20160601	<i>Element</i>
ContractSum	O	0..1	Type: sddb:ContractSum FractionDigits: 0 TotalDigits: 10 Format: sddb:Integer10 Description: Million Swedish kronor Name: Contract sum Example: 105	TotalDigits: 10 <i>Element</i>
GuaranteePeriod	O	0..1	Type: sddb:GuaranteePeriod FractionDigits: 0 TotalDigits: 5 Format: sddb:Integer5 Name: Guarantee period Example: 36	TotalDigits: 5 <i>Element</i>
ProjectOwner	M	1..1	Type: sddb:ProjectOwner Description: One of T6385 and T6001 must be used. Name: Project owner	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
ProjectOwningParty	O	0..1	Type: sddb:ProjectOwningParty Pattern: \d{13} Format: sddb:GLN Name: Project owning party Example: 7381020000036	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 85214	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Byggentreprenader Väst	<i>Element</i>
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department Example: 3	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Name: Street name Example: Lillavägen 1	<i>Element</i>
Building	O	0..1	Type: sddb:Building Length: 0 .. 35 Format: sddb:Building Name: Building Example: 5	<i>Element</i>
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Name: Postal box number Example: 73	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Name: City name Example: Staden	<i>Element</i>
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Name: Postal code Example: 45678	<i>Element</i>
CountryCode	O	0..1	Type: sddb:CountryCode	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	
InvoiceeNeB	O	0..1	Type: sddb:InvoiceeNeB Name: Invoice	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Invoicee	O	0..1	Type: sddb:Invoicee Pattern: \d{13} Format: sddb:GLN Name: Invoice Example: 7381030000067	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
PartyIdentifier	O	0..1	Type: sddb:PartyIdentifier Length: 0 .. 35 Format: sddb:PartyIdentifier Name: Partner Identifier Example: 7655678	<i>Element</i>
PartyName	O	0..1	Type: sddb:PartyName Length: 0 .. 35 Format: sddb:PartyName Name: Party name Example: Factoring AB	<i>Element</i>
Department	O	0..1	Type: sddb:Department Length: 0 .. 35 Format: sddb:Department Name: Department Example: Ekonomiavd	<i>Element</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Description: Invoice address Name: Street name Example: Fakturavägen 1	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
PostalBoxNumber	O	0..1	Type: sddb:PostalBoxNumber Length: .. 35 Format: sddb:PostalBoxNumber Description: Invoice address Name: Postal box number Example: 1	Element
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Description: Invoice address Name: City name Example: Fstad	Element
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Description: Invoice address Name: Postal code Example: 42159	Element
CountryCode	O	0..1	Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	Element
DeliveryNeB	O	0..1	Type: sddb:DeliveryNeB Description: If other than project owning party. Name: Delivery party	Element
xs:sequence	M	1..1	Type:	ContentModel
DeliveryParty	O	0..1	Type: sddb:DeliveryParty Pattern: \d{13} Format: sddb:GLN Name: Delivery party Example: 738105000041	Element
DeliveryPlaceLocation	O	0..1	Type: sddb:DeliveryPlaceLocation Format: xs:string Name: Place of delivery, specified	Element

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
EntryCode	O	0..1	Example: Xstad Type: sddb:EntryCode Length: 0 .. 12 Format: sddb:String12 Name: Entry code Example: 4598	<i>Element</i>
AddressNeB	O	0..1	Type: sddb:AddressNeB Name: Id number/Name and address	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
StreetName	O	0..1	Type: sddb:StreetName Length: 0 .. 35 Format: sddb:StreetName Name: Street name Example: Tallvägen	<i>Element</i>
CityName	O	0..1	Type: sddb:CityName Length: 0 .. 35 Format: sddb:CityName Name: City name Example: Xstad	<i>Element</i>
PostalCodeNeB	O	0..1	Type: sddb:PostalCodeNeB Length: 0 .. 17 Format: sddb:String17 Name: Postal code Example: 23192	<i>Element</i>
CountryCode	O	0..1	Type: sddb:CountryCode Length: .. 3 Format: sddb:CountryBaseType Name: Country, coded Example: SE	<i>Element</i>
ReceiverCoordinateX	O	0..1	Type: sddb:ReceiverCoordinateX Length: 0 .. 25 Format: sddb:String25 Name: Receiver coordinate X Example: 18.06468	<i>Element</i>
ReceiverCoordinateY	O	0..1	Type: sddb:ReceiverCoordinateY Length: 0 .. 25	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Format: sddb:String25 Name: Receiver coordinate Y Example: 59.330619	
DeliveryContact	O	0..1	Type: sddb:DeliveryContact Name: Delivery contact	<i>Element</i>
xs:sequence	M	1..1	Type: sddb:Name	<i>ContentModel</i>
Name	O	0..1	Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Karla Svensson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4687652220	<i>Element</i>
SMSNumber	O	0..1	Type: sddb:SMSNumber Length: 0 .. 25 Format: sddb:String25 Name: SMS number Example: +46709382695	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: karla@skoogs.se	<i>Element</i>
ProjectContact1SiteManager	O	0..1	Type: sddb:ProjectContact1SiteManager Name: Project contact 1, Site manager	<i>Element</i>
xs:sequence	M	1..1	Type: sddb:Name	<i>ContentModel</i>
Name	O	0..1	Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Lena Nilsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
			Format: sddb:String25 Name: Phone number Example: +4682251590	
— EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512	<i>Element</i>
— ID06	O	0..1	Name: Email address Example: lena@byggentreprenader.se Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
— ProjectContact2ProjectPurchaser	O	0..1	Name: Identification code ID06 Example: AA-0711-123456 Type: sddb:ProjectContact2ProjectPurchaser	<i>Element</i>
— xs:sequence	M	1..1	Name: Project contact 2, Project Purchaser Type: sddb:ProjectContact2ProjectPurchaser	<i>ContentModel</i>
— Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
— PhoneNumber	O	0..1	Name: Name Example: Eva Svensson Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25	<i>Element</i>
— EmailAddress	O	0..1	Name: Phone number Example: +4682251591 Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512	<i>Element</i>
— ID06	O	0..1	Name: Email address Example: eva@byggentreprenader.se Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35	<i>Element</i>
			Name: Identification code ID06 Example: AB-0711-123467	

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
ProjectContact3ProjectManager	O	0..1	Type: sddb:ProjectContact3ProjectManager Name: Project contact 3, Project manager	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Erik Larsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4682251592	<i>Element</i>
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: erik@byggentreprenader.se	<i>Element</i>
ID06	O	0..1	Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06 Example: AC-0711-123478	<i>Element</i>
ProjectContact4ProductionManager	O	0..1	Type: sddb:ProjectContact4ProductionManager Name: Project contact 4, Production manager	<i>Element</i>
xs:sequence	M	1..1	Type:	<i>ContentModel</i>
Name	O	0..1	Type: sddb:Name Length: 0 .. 35 Format: sddb:String35 Name: Name Example: Sven Nilsson	<i>Element</i>
PhoneNumber	O	0..1	Type: sddb:PhoneNumber Length: 0 .. 25 Format: sddb:String25 Name: Phone number Example: +4682251593	<i>Element</i>

St = Status: M=Mandatory, O=Optional

XML Guideline

Elements	St	Occurrence	Annotations	
EmailAddress	O	0..1	Type: sddb:EmailAddress Length: 0 .. 512 Format: sddb:String512 Name: Email address Example: sven@byggentreprenader.se	<i>Element</i>
ID06	O	0..1	Type: sddb:ID06 Length: 0 .. 35 Format: sddb:String35 Name: Identification code ID06 Example: AD-0711-123489	<i>Element</i>

St = Status: M=Mandatory, O=Optional